


6.006- *Introduction to Algorithms*



Lecture 21

Prof. Constantinos Daskalakis

CLRS 15

Menu

- Text Justification
- Structured Dynamic Programming
 - Vertex Cover on trees
 - Parsimony: recovering the tree of life

Menu

- Text Justification
- Structured Dynamic Programming
 - Vertex Cover on trees
 - Parsimony: recovering the tree of life

Text Justification – Word Processing

- A user writes stream of text
- WP has to break it into lines that aren't too long
- obvious algorithm => greedy:
 - put as much on first line as possible
 - then continue to lay out rest
 - used by MSWord, OpenOffice
- Problem: suboptimal layouts !!

e.g. blah blah blah blah blah
 b l a h vs blah blah
 reallylongword reallylongword

A Better Approach

- define a scoring rule
 - takes as input partition of words into lines
 - measures how good the layout is
- not an algorithm, just a metric
- find the layout with best score
 - here's where you think of algorithm

Layout Function

- Want to penalize big spaces. What objective would do that?
 - sum of leftover spaces?
 - then

blah blah blah
b l a h
reallylongword

 as good as

blah	blah
blah	blah
reallylongword	
 - i.e. it's the same for two layouts with the same number of lines (just total space minus number of characters)
- should penalize big spaces “extra”
 - (LaTeX uses sum of cubes of leftovers)

Formally

- input: array of words (lengths) $w[0..n]$
- split into lines $L_1, L_2 \dots$
- **badness of a line:**
$$\text{badness}(L) = (\text{page width} - \text{total length}(L))^3$$

– (or ∞ if total length of line $>$ page width)
- **objective:** break into lines $L_1, L_2 \dots$ minimizing $\sum_i \text{badness}(L_i)$

Can We DP?


- Subproblems?
 - $DP[i] = \text{min badness for words } w[i:n]$
(i.e. the score of the best layout of words $w[i], \dots, w[n]$)
 - n subproblems where n is number of words
- Decision for problem i ?
 - where to end first line in optimal layout for words $w[i:n]$
- Recurrence?
 - $DP[i] = \min_{j \text{ in range}(i+1, n)} (\text{badness}(w[i:j]) + DP[j])$
 - $DP[n+1] = 0$
 - $OPT = DP[0]$
- Runtime? $O(n^2)$?

Menu

- Text Justification
- Structured Dynamic Programming
 - Vertex Cover on trees
 - Parsimony: recovering the tree of life


Vertex cover

- Find a minimum set of vertices that contains at least one endpoint of each edge
- (like placing guards in a house to guard all corridors)
- NP-hard in general



Vertex cover

- Find a minimum set of vertices that contains at least one endpoint of each edge
- (like placing guards in a house to guard all corridors)
- NP-hard in general
- We will see a polynomial (in n) time algorithm for trees of size n
- Ideas ?



Vertex cover: algorithm

- Let $\text{cost}(v,b)$ be the min-cost solution of the sub-tree rooted at v , assuming v 's status is $b \in \{\text{YES}, \text{NO}\}$

- Recurrence for $\text{cost}(v,b)$

$$\text{cost}(v, \text{YES}) = 1 + \min_{b_1} \text{cost}(u_1, b_1) + \min_{b_2} \text{cost}(u_2, b_2) + \dots$$


$$\text{cost}(v, \text{NO}) = \text{cost}(u_1, \text{YES}) + \text{cost}(u_2, \text{YES}) + \dots$$

- Base case $v = \text{leaf}$:

$$\text{cost}(v, \text{YES}) = 1$$


$$\text{cost}(v, \text{NO}) = 0$$

- Running time ? $O(n)$



The Tree of Life

- 3 million years




time

today

The Computational Problem

- 3 million years




time

today

The Computational Problem

- 3 million years




How to score a proposed tree?

- A desired property of a plausible tree:

Explains how the observed DNA sequences came about using few mutations.

- Such tree has “**high parsimony**”.
- Algorithmic problem. Given:
 - n “leaf strings” of length m each, with letters from {A, C, G, T}
 - a tree
- Goal: find “**inner node**” sequences that minimize the sum of all mutations along all edges




parsimony = 5

- This is the **parsimony** of the tree.
- Algorithmic Ideas ?

Parsimony: algorithm

- Observation I: we can consider one letter at a time
- Observation II: can use dynamic programming to find the best inner-node letters



Parsimony: dynamic program

- Define letter distance as follows


$$D(a,b)=0 \text{ if } a=b \text{ and } =1 \text{ otherwise}$$

- For any node v of the tree and label L in $\{A, C, G, T\}$, define $\text{cost}(v,L)$

- This is the minimum cost for the subtree rooted at v , if v is labeled L

- solution = $\min_L \text{cost}(\text{root}, L)$

- Recurrence for $\text{cost}(v,L)$?



$$\text{cost}(v,L) = \min_{L1, L2} D(L, L1) + D(L, L2) + \text{cost}(u1, L1) + \text{cost}(u2, L2)$$

- Base case: if v is a leaf

$$\text{cost}(v,L) = \infty * D(L, \text{leaf_label}(v))$$

Parsimony: analysis

- We have

$$\text{cost}(v, L) = \min_{L_1, L_2} D(L, L_1) + D(L, L_2) + \text{cost}(u_1, L_1) + \text{cost}(u_2, L_2)$$


- Equivalently

$$\text{cost}(v, L) = \min_{L_1} D(L, L_1) + \text{cost}(u_1, L_1) + \min_{L_2} D(L, L_2) + \text{cost}(u_2, L_2)$$

- Running time?

$$O(n k) * O(k) = O(nk^2)$$

where k is the alphabet size



Time for digression (extracurricular)

- Back to vertex cover
- What if the graph is not a tree ?
- Small separator good enough

