


LOGICAL AGENTS

CHAPTER 7

Outline

- ◇ Knowledge-based agents
- ◇ Wumpus world
- ◇ Logic in general—models and entailment
- ◇ Propositional (Boolean) logic
- ◇ Equivalence, validity, satisfiability
- ◇ Inference rules and theorem proving
 - forward chaining
 - backward chaining
 - resolution



Knowledge base = set of sentences in a **formal** language

Declarative approach to building an agent (or other system):

TELL it what it needs to know

Then it can **ASK** itself what to do—answers should follow from the KB

Agents can be viewed at the **knowledge level**

i.e., **what they know**, regardless of how implemented

Or at the **implementation level**

i.e., data structures in KB and algorithms that manipulate them

A simple knowledge-based agent

```
function KB-AGENT(percept) returns an action  
  static: KB, a knowledge base  
           t, a counter, initially 0, indicating time  
  TELL(KB, MAKE-PERCEPT-SENTENCE(percept, t))  
  action ← ASK(KB, MAKE-ACTION-QUERY(t))  
  TELL(KB, MAKE-ACTION-SENTENCE(action, t))  
  t ← t + 1  
  return action
```

The agent must be able to:

Represent states, actions, etc.

Incorporate new percepts

Update internal representations of the world

Deduce hidden properties of the world

Deduce appropriate actions

Wumpus World PEAS description

Performance measure

gold +1000, death -1000

-1 per step, -10 for using the arrow

Environment

Squares adjacent to wumpus are smelly

Squares adjacent to pit are breezy


Glitter iff gold is in the same square

Shooting kills wumpus if you are facing it

Shooting uses up the only arrow

Grabbing picks up gold if in same square

Releasing drops the gold in same square



Actuators Left turn, Right turn,

Forward, Grab, Release, Shoot

Sensors Breeze, Glitter, Smell

Wumpus world characterization

Observable??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic?? No—sequential at the level of actions

Static??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic?? No—sequential at the level of actions

Static?? Yes—Wumpus and Pits do not move

Discrete??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic?? No—sequential at the level of actions

Static?? Yes—Wumpus and Pits do not move

Discrete?? Yes

Single-agent??

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic?? No—sequential at the level of actions

Static?? Yes—Wumpus and Pits do not move


Discrete?? Yes

Single-agent?? Yes—Wumpus is essentially a natural feature


Exploring a wumpus world

OK			
OK A	OK		


Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world



Exploring a wumpus world




Other tight spots



Breeze in (1,2) and (2,1)
 \Rightarrow no safe actions

Assuming pits uniformly distributed,
 (2,2) has pit w/ prob 0.86, vs. 0.31

Smell in (1,1)
 \Rightarrow cannot move



Can use a strategy of **coercion**:
 shoot straight ahead
 wumpus was there \Rightarrow dead \Rightarrow safe
 wumpus wasn't there \Rightarrow safe

Entailment

Entailment means that one thing **follows from** another:

$$KB \models \alpha$$

Knowledge base KB entails sentence α
if and only if
 α is true in all worlds where KB is true

E.g., the KB containing “the Giants won” and “the Reds won”
entails “Either the Giants won or the Reds won”

E.g., $x + y = 4$ entails $4 = x + y$

Entailment is a relationship between sentences (i.e., **syntax**)
that is based on **semantics**

Note: brains process **syntax** (of some sort)

Models


Logicians typically think in terms of **models**, which are formally structured worlds with respect to which truth can be evaluated

We say m is a **model** of a sentence α if α is true in m

$M(\alpha)$ is the set of all models of α

Then $KB \models \alpha$ if and only if $M(KB) \subseteq M(\alpha)$

E.g. $KB =$ Giants won and Reds won
 $\alpha =$ Giants won




Entailment in the wumpus world









Situation after detecting nothing in [1,1],
moving right, breeze in [2,1]

Consider possible models for ?s
assuming only pits


3 Boolean choices \Rightarrow 8 possible models



Wumpus models




Wumpus models



KB = wumpus-world rules + observations

Wumpus models



KB = wumpus-world rules + observations

α_1 = “[1,2] is safe”, $KB \models \alpha_1$, proved by model checking

Logic in general

Logics are formal languages for representing information such that conclusions can be drawn

Syntax defines the sentences in the language

Semantics define the “meaning” of sentences; i.e., define truth of a sentence in a world

E.g., the language of arithmetic


$x + 2 \geq y$ is a sentence; $x^2 + y >$ is not a sentence

$x + 2 \geq y$ is true iff the number $x + 2$ is no less than the number y

$x + 2 \geq y$ is true in a world where $x = 7, y = 1$


$x + 2 \geq y$ is false in a world where $x = 0, y = 6$

Wumpus models



KB = wumpus-world rules + observations

Wumpus models



KB = wumpus-world rules + observations

α_2 = “[2,2] is safe”, $KB \not\models \alpha_2$

Inference

$KB \vdash_i \alpha$ = sentence α can be derived from KB by procedure i

Consequences of KB are a haystack; α is a needle.

Entailment = needle in haystack; inference = finding it

Soundness: i is sound if

whenever $KB \vdash_i \alpha$, it is also true that $KB \models \alpha$

Completeness: i is complete if

whenever $KB \models \alpha$, it is also true that $KB \vdash_i \alpha$

Preview: we will define a logic (first-order logic) which is expressive enough to say almost anything of interest, and for which there exists a sound and complete inference procedure.

That is, the procedure will answer any question whose answer follows from what is known by the KB .

Propositional logic: Syntax

Propositional logic is the simplest logic—illustrates basic ideas

The proposition symbols P_1, P_2 etc are sentences

If S is a sentence, $\neg S$ is a sentence (negation)

If S_1 and S_2 are sentences, $S_1 \wedge S_2$ is a sentence (conjunction)

If S_1 and S_2 are sentences, $S_1 \vee S_2$ is a sentence (disjunction)

If S_1 and S_2 are sentences, $S_1 \Rightarrow S_2$ is a sentence (implication)

If S_1 and S_2 are sentences, $S_1 \Leftrightarrow S_2$ is a sentence (biconditional)

Propositional logic: Semantics

Each model specifies true/false for each proposition symbol

E.g. $P_{1,2}$ $P_{2,2}$ $P_{3,1}$
true true false

(With these symbols, 8 possible models, can be enumerated automatically.)

Rules for evaluating truth with respect to a model m :

$\neg S$ is true iff	S	is false
$S_1 \wedge S_2$ is true iff	S_1	is true and S_2 is true
$S_1 \vee S_2$ is true iff	S_1	is true or S_2 is true
$S_1 \Rightarrow S_2$ is true iff	S_1	is false or S_2 is true
i.e., is false iff	S_1	is true and S_2 is false
$S_1 \Leftrightarrow S_2$ is true iff	$S_1 \Rightarrow S_2$ is true	and $S_2 \Rightarrow S_1$ is true

Simple recursive process evaluates an arbitrary sentence, e.g.,

$\neg P_{1,2} \wedge (P_{2,2} \vee P_{3,1}) = \textit{true} \wedge (\textit{false} \vee \textit{true}) = \textit{true} \wedge \textit{true} = \textit{true}$

Truth tables for connectives

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>
<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>
<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>

Wumpus world sentences

Let $P_{i,j}$ be true if there is a pit in $[i, j]$.

Let $B_{i,j}$ be true if there is a breeze in $[i, j]$.

$$\neg P_{1,1}$$

$$\neg B_{1,1}$$

$$B_{2,1}$$

“Pits cause breezes in adjacent squares”

Wumpus world sentences

Let $P_{i,j}$ be true if there is a pit in $[i, j]$.

Let $B_{i,j}$ be true if there is a breeze in $[i, j]$.

$$\neg P_{1,1}$$

$$\neg B_{1,1}$$

$$B_{2,1}$$

“Pits cause breezes in adjacent squares”

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

$$B_{2,1} \Leftrightarrow (P_{1,1} \vee P_{2,2} \vee P_{3,1})$$

“A square is breezy **if and only if** there is an adjacent pit”

Truth tables for inference

$B_{1,1}$	$B_{2,1}$	$P_{1,1}$	$P_{1,2}$	$P_{2,1}$	$P_{2,2}$	$P_{3,1}$	R_1	R_2	R_3	R_4	R_5	KB
<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>false</i>
<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<u><i>true</i></u>
<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<u><i>true</i></u>
<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<u><i>true</i></u>
<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>false</i>

Enumerate rows (different assignments to symbols),
 if **KB** is true in row, check that α is too

Inference by enumeration

Depth-first enumeration of all models is sound and complete

function **TT-ENTAILS?**(KB, α) **returns** *true* or *false*

inputs: KB , the knowledge base, a sentence in propositional logic

α , the query, a sentence in propositional logic

$symbols \leftarrow$ a list of the proposition symbols in KB and α

return TT-CHECK-ALL($KB, \alpha, symbols, []$)

function **TT-CHECK-ALL**($KB, \alpha, symbols, model$) **returns** *true* or *false*

if EMPTY?($symbols$) **then**

if PL-TRUE?($KB, model$) **then return** PL-TRUE?($\alpha, model$)

else return *true*

else do

$P \leftarrow$ FIRST($symbols$); $rest \leftarrow$ REST($symbols$)

return TT-CHECK-ALL($KB, \alpha, rest, EXTEND(P, true, model)$) **and**

 TT-CHECK-ALL($KB, \alpha, rest, EXTEND(P, false, model)$)

$O(2^n)$ for n symbols; problem is **co-NP-complete**

Logical equivalence

Two sentences are **logically equivalent** iff true in same models:

$\alpha \equiv \beta$ if and only if $\alpha \models \beta$ and $\beta \models \alpha$

$(\alpha \wedge \beta) \equiv (\beta \wedge \alpha)$	commutativity of \wedge
$(\alpha \vee \beta) \equiv (\beta \vee \alpha)$	commutativity of \vee
$((\alpha \wedge \beta) \wedge \gamma) \equiv (\alpha \wedge (\beta \wedge \gamma))$	associativity of \wedge
$((\alpha \vee \beta) \vee \gamma) \equiv (\alpha \vee (\beta \vee \gamma))$	associativity of \vee
$\neg(\neg\alpha) \equiv \alpha$	double-negation elimination
$(\alpha \Rightarrow \beta) \equiv (\neg\beta \Rightarrow \neg\alpha)$	contraposition
$(\alpha \Rightarrow \beta) \equiv (\neg\alpha \vee \beta)$	implication elimination
$(\alpha \Leftrightarrow \beta) \equiv ((\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha))$	biconditional elimination
$\neg(\alpha \wedge \beta) \equiv (\neg\alpha \vee \neg\beta)$	De Morgan
$\neg(\alpha \vee \beta) \equiv (\neg\alpha \wedge \neg\beta)$	De Morgan
$(\alpha \wedge (\beta \vee \gamma)) \equiv ((\alpha \wedge \beta) \vee (\alpha \wedge \gamma))$	distributivity of \wedge over \vee
$(\alpha \vee (\beta \wedge \gamma)) \equiv ((\alpha \vee \beta) \wedge (\alpha \vee \gamma))$	distributivity of \vee over \wedge

Conversion to CNF

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

1. Eliminate \Leftrightarrow , replacing $\alpha \Leftrightarrow \beta$ with $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$.

$$(B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

2. Eliminate \Rightarrow , replacing $\alpha \Rightarrow \beta$ with $\neg\alpha \vee \beta$.

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg(P_{1,2} \vee P_{2,1}) \vee B_{1,1})$$

3. Move \neg inwards using de Morgan's rules and double-negation:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge ((\neg P_{1,2} \wedge \neg P_{2,1}) \vee B_{1,1})$$

4. Apply distributivity law (\vee over \wedge) and flatten:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg P_{1,2} \vee B_{1,1}) \wedge (\neg P_{2,1} \vee B_{1,1})$$

Validity and satisfiability

A sentence is **valid** if it is true in **all** models,

e.g., *True*, $A \vee \neg A$, $A \Rightarrow A$, $(A \wedge (A \Rightarrow B)) \Rightarrow B$

Validity is connected to inference via the **Deduction Theorem**:

$KB \models \alpha$ if and only if $(KB \Rightarrow \alpha)$ is valid

A sentence is **satisfiable** if it is true in **some** model

e.g., $A \vee B$, C

A sentence is **unsatisfiable** if it is true in **no** models

e.g., $A \wedge \neg A$

Satisfiability is connected to inference via the following:

$KB \models \alpha$ if and only if $(KB \wedge \neg \alpha)$ is unsatisfiable

i.e., prove α by *reductio ad absurdum*

Proof methods

Proof methods divide into (roughly) two kinds:

Application of inference rules

- Legitimate (sound) generation of new sentences from old
- **Proof** = a sequence of inference rule applications
 - Can use inference rules as operators in a standard search alg.
- Typically require translation of sentences into a **normal form**

Model checking

- truth table enumeration (always exponential in n)
- improved backtracking, e.g., Davis–Putnam–Logemann–Loveland
- heuristic search in model space (sound but incomplete)
 - e.g., min-conflicts-like hill-climbing algorithms

Forward and backward chaining

Horn Form (restricted)

KB = **conjunction** of **Horn clauses**

Horn clause =

◇ proposition symbol; or

◇ (conjunction of symbols) \Rightarrow symbol

E.g., $C \wedge (B \Rightarrow A) \wedge (C \wedge D \Rightarrow B)$

Modus Ponens (for Horn Form): complete for Horn KBs

$$\frac{\alpha_1, \dots, \alpha_n, \quad \alpha_1 \wedge \dots \wedge \alpha_n \Rightarrow \beta}{\beta}$$

Can be used with **forward chaining** or **backward chaining**.
These algorithms are very natural and run in **linear** time

Forward chaining

Idea: fire any rule whose premises are satisfied in the *KB*,
add its conclusion to the *KB*, until query is found

$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$


$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A

B




Forward chaining algorithm

```
function PL-FC-ENTAILS?(KB, q) returns true or false
  inputs: KB, the knowledge base, a set of propositional Horn clauses
           q, the query, a proposition symbol
  local variables: count, a table, indexed by clause, initially the number of premises
                    inferred, a table, indexed by symbol, each entry initially false
                    agenda, a list of symbols, initially the symbols known in KB


  while agenda is not empty do
    p ← POP(agenda)
    unless inferred[p] do
      inferred[p] ← true
      for each Horn clause c in whose premise p appears do
        decrement count[c]
        if count[c] = 0 then do
          if HEAD[c] = q then return true
          PUSH(HEAD[c], agenda)

  return false
```


Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example



Forward chaining example



Forward chaining example



Proof of completeness

FC derives every atomic sentence that is entailed by KB

1. FC reaches a **fixed point** where no new atomic sentences are derived
2. Consider the final state as a model m , assigning true/false to symbols

3. Every clause in the original KB is true in m

Proof: Suppose a clause $a_1 \wedge \dots \wedge a_k \Rightarrow b$ is false in m

Then $a_1 \wedge \dots \wedge a_k$ is true in m and b is false in m

Therefore the algorithm has not reached a fixed point!

4. Hence m is a model of KB

5. If $KB \models q$, q is true in **every** model of KB , including m

General idea: construct any model of KB by sound inference, check α

Backward chaining

Idea: work backwards from the query q :

to prove q by BC,

check if q is known already, or

prove by BC all premises of some rule concluding q


Avoid loops: check if new subgoal is already on the goal stack

Avoid repeated work: check if new subgoal


1) has already been proved true, or

2) has already failed


Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example



Backward chaining example



Backward chaining example



Forward vs. backward chaining

FC is **data-driven**, cf. automatic, unconscious processing,
e.g., object recognition, routine decisions

May do lots of work that is irrelevant to the goal

BC is **goal-driven**, appropriate for problem-solving,
e.g., Where are my keys? How do I get into a PhD program?

Complexity of BC can be **much less** than linear in size of KB

Resolution

Conjunctive Normal Form (CNF—universal)

conjunction of **disjunctions** of **literals**
clauses

E.g., $(A \vee \neg B) \wedge (B \vee \neg C \vee \neg D)$


Resolution inference rule (for CNF): complete for propositional logic

$$\frac{l_1 \vee \dots \vee l_k, \quad m_1 \vee \dots \vee m_n}{l_1 \vee \dots \vee l_{i-1} \vee l_{i+1} \vee \dots \vee l_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n}$$

where l_i and m_j are complementary literals. E.g.,

$$\frac{P_{1,3} \vee P_{2,2}, \quad \neg P_{2,2}}{P_{1,3}}$$

Resolution is sound and complete for propositional logic



Conversion to CNF

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

1. Eliminate \Leftrightarrow , replacing $\alpha \Leftrightarrow \beta$ with $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$.

$$(B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

2. Eliminate \Rightarrow , replacing $\alpha \Rightarrow \beta$ with $\neg\alpha \vee \beta$.

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg(P_{1,2} \vee P_{2,1}) \vee B_{1,1})$$

3. Move \neg inwards using de Morgan's rules and double-negation:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge ((\neg P_{1,2} \wedge \neg P_{2,1}) \vee B_{1,1})$$

4. Apply distributivity law (\vee over \wedge) and flatten:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg P_{1,2} \vee B_{1,1}) \wedge (\neg P_{2,1} \vee B_{1,1})$$


Resolution algorithm

Proof by contradiction, i.e., show $KB \wedge \neg\alpha$ unsatisfiable

```
function PL-RESOLUTION( $KB, \alpha$ ) returns true or false
  inputs:  $KB$ , the knowledge base, a sentence in propositional logic
            $\alpha$ , the query, a sentence in propositional logic
   $clauses \leftarrow$  the set of clauses in the CNF representation of  $KB \wedge \neg\alpha$ 
   $new \leftarrow \{ \}$ 
  loop do
    for each  $C_i, C_j$  in  $clauses$  do
       $resolvents \leftarrow$  PL-RESOLVE( $C_i, C_j$ )
      if  $resolvents$  contains the empty clause then return true
       $new \leftarrow new \cup resolvents$ 
  if  $new \subseteq clauses$  then return false
   $clauses \leftarrow clauses \cup new$ 
```

Resolution example

$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$



Summary

Logical agents apply **inference** to a **knowledge base** to derive new information and make decisions

Basic concepts of logic:

- **syntax**: formal structure of **sentences**
- **semantics**: **truth** of sentences wrt **models**
- **entailment**: necessary truth of one sentence given another
- **inference**: deriving sentences from other sentences
- **soundness**: derivations produce only entailed sentences
- **completeness**: derivations can produce all entailed sentences

Wumpus world requires the ability to represent partial and negated information, reason by cases, etc.

Forward, backward chaining are linear-time, complete for Horn clauses
Resolution is complete for propositional logic

Propositional logic lacks expressive power